



TECHNICAL REPORT

Calculation Method for the
Performance of Anchor Channels
under Fatigue Loading

TR 050
October 2018

Contents

1	SCOPE OF THE TECHNICAL REPORT	3
1.1	General	3
1.2	Type, dimensions and materials of anchor channels	3
1.3	Anchor channel loading	4
1.4	Specific terms used in this TR.....	5
2	COMBINATION OF STATIC AND CYCLIC LOADS AND INFLUENCE RANGES	7
3	FATIGUE DESIGN OF ANCHOR CHANNELS	9
3.1	Design concept	9
3.2	Design method I – Complete method.....	11
3.2.1	Conditions of applicability	11
3.2.2	Calculation of fatigue resistance, ΔNR_d, E, n, in relation to the lower cyclic load, NE_{lod}	12
3.2.3	Required verifications for design	13
3.3	Design method II – Simplified method.....	13
3.3.1	Conditions of applicability	13
3.3.2	Required verifications for design	13
4	REFERENCE DOCUMENTS.....	14

1 SCOPE OF THE TECHNICAL REPORT

1.1 General

The construction of the anchor channel system is vitally important for its load bearing capacity and serviceability. Constructive measures are recommended to minimize influences on the load bearing behavior by unexpected displacements.

Uncontrolled displacements have to be limited to fulfil the increased serviceability requirements in particular at pulsating cyclic loading. Slip has to be generally avoided.

This Technical Report contains a design method for anchor channels under fatigue cyclic tension loading which have been awarded an ETA in accordance with EAD 330008 Anchor channels [3].

Note: This Technical Report is intended to provide a design method for anchor channels under fatigue cyclic tension loading and shall be used in conjunction with the static provisions of EN 1992-4 [2] or EOTA Technical Report 047 [4].

This document has been written to represent current best practice. However, users should verify that applying its provisions allows local regulatory requirements to be satisfied.

This Technical Report provides a design method for anchor channels under tension fatigue cyclic loading in combination with or without static or quasi-static loads in concrete members (connection between structural elements and attachment of non-structural elements to structural components). The anchor channel is used to transmit only tension loads into the concrete. No static or quasi-static shear or fatigue cyclic shear load may be applied in concomitance with a fatigue cyclic tension load.

This Technical Report provides a design method for anchor channels installed in members made of compacted normal weight concrete of strength classes in the range C20/25 to C90/105 all in accordance with EN 206-1 [5]. The anchor channel is intended to be used in cracked and non-cracked concrete.

This Technical Report is intended for safety related applications in which the failure of anchor channels may result in collapse or partial collapse of the structure, cause risk to human life or lead to significant economic loss. In this context it also covers non-structural elements.

The design rules in this Technical Report are only valid for anchor channels with a European Technical Assessment (ETA) with characteristic resistance under fatigue cyclic loading on basis of EAD 330008 [3].

The transfer of the loads applied to the anchor channel to the supports of the concrete member shall be shown for both, ultimate limit state and serviceability limit state according to EN 1992-1-1 [1].

This Technical Report does not cover the design of the fixture. The design of the fixture shall be carried out to comply with the appropriate Standards and fulfil the requirements on the fixture as given in this Technical Report.

This document relies on characteristic resistances and distances which are stated in an ETA and referred to in this Technical Report.

1.2 Type, dimensions and materials of anchor channels

This Technical Report applies to anchor channels with rigid connection (e.g. welded, forged, bolted) between anchor and channel. The anchor channels shall have an established suitability for the specified application in concrete, which is stated in the relevant ETA.

The effective embedment depth shall be $h_{ef} \geq 40$ mm.

This Technical Report covers anchor channels made of either carbon steel or stainless steel. The surface of the steel may be coated or uncoated. This Technical Report is valid for anchor channels with a nominal steel tensile strength $f_{uk} \leq 1000$ N/mm².

1.3 Anchor channel loading

In general, fatigue verification is required when more than or equal to 1000 load cycles are expected for pulsation tension loads on the anchor channel.

In general all types of actions occurring during the period of intended use of an anchor channel shall be taken into account for the design. Typically harmonic and/or periodic actions including different (peak-to-peak) amplitudes are considered in the context of fatigue cyclic loading. Harmonic and periodic actions can consist of:

- Oscillations touching zero,
- Oscillations with the same algebraic sign.

Cyclic loads may consist of a single constant or different amplitudes. When different amplitudes need to be taken into account, the sequence of loading may be converted into a collective action of one load level with an equivalent grade of damage by using the Miner's Rule [6]. An example of such a resulting collective action or a single constant amplitude load cycle is given in Figure 1.3.

For the overall fatigue design process, the knowledge of the S-N-curve or, at a minimum, the fatigue limit resistance, is required and the design methods I and/or II as shown in Section 3 of this document can be used.




Figure 1.3 Definition of force of load cycle (N_{up} = maximum (upper) cyclic load; N_{lo} = minimum (lower) cyclic load, N_m = mean load, ΔN = cyclic (peak-to-peak range) load)

The assignment between design method and test method is shown in Table 1.1. The test method is stated in the European Technical Assessment (ETA).

Table 1.1: Test methods and related design methods for fatigue cyclic loading

		Test Method		
		A1 Continuous function of fatigue resistance depending on number of load cycles	A2 Tri-linear function of fatigue resistance depending on number of load cycles	B Fatigue limit resistance
Design Method	Method I	X	X	not applicable
	Method II	X	X	X

1.4 Specific terms used in this TR

Indices

E	static action / quasi-static action
N	normal force
R	resistance
M	material
n	number of load cycles or oscillations
k	characteristic value
d	design values
s	steel
c	concrete cone
p	concrete pull-out
up	upper
lo	lower

Actions

N_{Ed}	design static or quasi-static load
$N_{Elo d}$	design lower cyclic load
ΔN_{Ed}	design fatigue cyclic load
$N_{Eup d}$	$= N_{Elo d} + \Delta N_{Ed}$, design upper cyclic load
$N_{Ed,eq}$	equivalent static design action calculated in accordance with EN 1992-4 [2] or Technical Report 047 [4]
$\Delta N_{Ed,eq}$	equivalent design fatigue cyclic load

Resistances

N_{Rk}	characteristic static resistance
N_{Rd}	design static resistance
ΔN_{Rk}	characteristic fatigue resistance
ΔN_{Rd}	design fatigue resistance
$\Delta N_{Rk,0,n}$	Characteristic fatigue resistance with origin load ($N_{Elo d} = 0$) and n load cycles taken from the ETA
$\Delta N_{Rk,s,0,n}$	Characteristic tensile steel fatigue resistance with origin load ($N_{Elo d} = 0$) and n load cycles taken from the ETA
$\Delta N_{Rk,p,0,n}$	Characteristic concrete pull-out fatigue resistance with origin load ($N_{Elo d} = 0$) and n load cycles taken from the ETA
$\Delta N_{Rk,c,0,n}$	Characteristic concrete cone fatigue resistance with origin load ($N_{Elo d} = 0$) and n load cycles taken from the ETA
$\Delta N_{Rk,0,\infty}$	Characteristic fatigue limit resistance with origin load ($N_{Elo d} = 0$) taken from the ETA
$\Delta N_{Rk,s,0,\infty}$	Characteristic tensile steel fatigue limit resistance with origin load ($N_{Elo d} = 0$) taken from the ETA
$\Delta N_{Rk,p,0,\infty}$	Characteristic concrete pull-out fatigue limit resistance with origin load ($N_{Elo d} = 0$) taken from the ETA
$\Delta N_{Rk,c,0,\infty}$	Characteristic concrete cone fatigue limit resistance with origin load ($N_{Elo d} = 0$) taken from the ETA

$\Delta N_{Rd,0,n}$	Design steel tensile fatigue resistance with origin load ($N_{Eload} = 0$) and n load cycles
$\Delta N_{Rd,s,0,n}$	Design steel tensile fatigue resistance with origin load ($N_{Eload} = 0$) and n load cycles
$\Delta N_{Rd,p,0,n}$	Design concrete pull-out fatigue resistance with origin load ($N_{Eload} = 0$) and n load cycles
$\Delta N_{Rd,c,0,n}$	Design concrete cone fatigue resistance with origin load ($N_{Eload} = 0$) and n load cycles
$\Delta N_{Rd,0,\infty}$	Design limit resistance with origin load ($N_{Eload} = 0$)
$\Delta N_{Rd,s,0,\infty}$	Design tensile steel fatigue limit resistance with origin load ($N_{Eload} = 0$)
$\Delta N_{Rd,p,0,\infty}$	Design concrete pull-out fatigue limit resistance with origin load ($N_{Eload} = 0$)
$\Delta N_{Rd,c,0,\infty}$	Design concrete cone fatigue limit resistance with origin load ($N_{Eload} = 0$)
$\Delta N_{Rd,E,n}$	Design fatigue resistance with ($N_{Eload} > 0$) and n load cycles
$\Delta N_{Rd,s,E,n}$	Design tensile steel fatigue resistance with ($N_{Eload} > 0$) and n load cycles
$\Delta N_{Rd,p,E,n}$	Design concrete pull-out fatigue resistance with ($N_{Eload} > 0$) and n load cycles
$\Delta N_{Rd,c,E,n}$	Design concrete cone fatigue resistance with ($N_{Eload} > 0$) and n load cycles
$\Delta N_{Rd,E,\infty}$	Design fatigue limit resistance with ($N_{Eload} > 0$)
$\Delta N_{Rd,s,E,\infty}$	Design tensile steel fatigue limit resistance with ($N_{Eload} > 0$)
$\Delta N_{Rd,p,E,\infty}$	Design concrete pullout fatigue limit resistance with ($N_{Eload} > 0$)
$\Delta N_{Rd,c,E,\infty}$	Design concrete cone fatigue limit resistance with ($N_{Eload} > 0$)

2 COMBINATION OF STATIC AND CYCLIC LOADS AND INFLUENCE RANGES

This Technical Report covers only combinations of static and cyclic tension loads perpendicular to the concrete surface. Load combinations including static and cyclic shear loads acting alone or in combination with any type of tension load are not covered in this Technical Report.


The range of influence of a single static tension load shall be taken into account according to Technical Report 047 [4] as shown in Figure 2.1.

The range of influence of a cyclic tension load is assumed to be different and is shown in Figure 2.2.

As shown in Figure 2.3, the equivalent static action, $N_{Ed,eq}$, and the equivalent fatigue action, $\Delta N_{Ed,eq}$, are calculated using linear superposition. This is applicable for single loads or multiple loads acting simultaneously on the anchor channel.


For the sake of simplicity, the equivalent static action, $N_{Ed,eq}$, and the equivalent fatigue action, $\Delta N_{Ed,eq}$, are assumed to be acting at the same location.

Based on the distribution of the equivalent static and fatigue actions, the corresponding static and fatigue load for the anchor under consideration can therefore be determined.




$$l_i = 13 \cdot I_y^{0,05} \cdot s^{0,5} \geq s \quad [\text{mm}]$$

Figure 2.1 Range of influence of a single static load



$$l_i = 13 \cdot I_y^{0,05} \cdot s^{0,5} \geq s \quad [\text{mm}]$$

Figure 2.2 Range of influence of a single cyclic load



$$l_i = 13 \cdot I_y^{0,05} \cdot s^{0,5} \geq s \quad [\text{mm}]$$

Figure 2.3 Example of multiple static and cyclic loads acting simultaneously

3 FATIGUE DESIGN OF ANCHOR CHANNELS

3.1 Design concept

For the design of anchor channels under fatigue cyclic action the concept of partial safety factors shall be applied. It shall be shown that the design actions, ΔE_d , do not exceed the design resistance, ΔR_d :

$$\Delta E_d \leq \Delta R_d \quad (3.1)$$

where: ΔE_d design action

ΔR_d design resistance

For the determination of the design actions, the following procedure shall be applied:

$$\Delta E_d = \gamma_{F, fat} \cdot \Delta E_k \quad (3.2)$$

where: ΔE_k characteristic action

$\gamma_{F, fat}$ partial safety factor for fatigue actions

The following partial safety factors for actions are recommended in absence of other national regulations.

$\gamma_{F, fat} = 1,0$ If there is a collective load with different levels of actions and the maximum value of actions, ΔE_{max} , is assumed for the design.

$\gamma_{F, fat} = 1,2$ If the effective (actual) collective action is converted by using the Miner's Rule [6] to a collective of one level with an equivalent level of damage or if the effective (actual) collective action is a collective of one load level.

The following partial safety factors for resistances are recommended for anchor channels under fatigue cyclic loading.

The values of the partial factors for anchor channels under fatigue cyclic loading for use in a Country may be found in its National Annex of EN 1992-4 [2]. For the determination of the design fatigue limit resistance it is recommended to take the partial factor for material as $\gamma_{M, fat} = 1,35$ for all modes of failure.

For the transition zone from the static bearing capacity (γ_M) up to the fatigue limit resistance ($\gamma_{M, fat}$), the partial safety factors are calculated as follows:

$$\gamma_{M, fat, n} = \gamma_{M, fat} + (\gamma_M - \gamma_{M, fat}) \cdot (\Delta N_{Rk, n} - \Delta N_{Rk, \infty}) / (N_{Rk} - \Delta N_{Rk, \infty}) \quad (3.3)$$

For the determination of the design fatigue limit resistance, the characteristic value determined by tests shall be divided with the partial safety factor $\gamma_{M, fat}$ (e.g., $\Delta N_{Rd} = \Delta N_{Rk} / \gamma_{M, fat}$).

For the transition zone from the static bearing capacity up to the fatigue limit resistance, the characteristic value determined by tests shall be divided with the partial safety factor $\gamma_{M, fat, n}$ (e.g., $\Delta N_{Rd, n} = \Delta N_{Rk, n} / \gamma_{M, fat, n}$).




The general form of the ultimate limit state verification with fatigue influence is as follows:

$$(\Delta N_{Ed} / \Delta N_{Rd}) \leq 1,0 \quad (3.4)$$

Each failure mode shall be verified separately.

The design of anchor channels with fatigue influence shall be conducted in accordance with the concept provided in Table 3.1. The equations in Section 3.2.3 – design method I - and Section 3.3.2 – design method II – shall be used.

Table 3.1 Concept for design of anchor channels with fatigue influence

Step	Result	Note
<p>1</p> <p>S-N-curve for design fatigue resistance with a lower cyclic load $N_{Elo d} = 0$ and n load cycles ($\Delta N_{Rd,0,n}$)</p>		<p>S-N-curves can be determined for each failure mode.</p> <p>At a minimum, the value of the fatigue limit resistance, ($\Delta N_{Rd,0,\infty}$), shall be given</p>
<p>2</p> <p>Goodman Diagram developed for a selected number of load cycles, n</p>		<p>The Goodman Diagram allows to establish the fatigue resistance, $\Delta N_{Rd,E,n}$, in relation to the lower cyclic load, $N_{Elo d}$, for a given number of load cycles, n</p>
<p>3</p> <p>Converted S-N-curves under pulsating load $N_{Elo d} > 0$</p>		<p>The conversion of the S-N-curves developed with zero or low minimum (lower) cyclic load (see step 1) into S-N-curves including different ($N_{Elo d} > 0$) lower cyclic loads is achieved by means of the Goodman Diagram (see step 2) for given number(s) of load cycles, n</p>
<p>4</p> <p>Design verifications: Steel failure Pull-out failure Concrete cone failure</p>	$\Delta N_{Ed} / \Delta N_{Rd,s,E,n} \leq 1,0$ $\Delta N_{Ed} / \Delta N_{Rd,p,E,n} \leq 1,0$ $\Delta N_{Ed} / \Delta N_{Rd,c,E,n} \leq 1,0$	<p>ΔN_{Ed} – design value of the applied load range</p>

3.2 Design method I – Complete method

3.2.1 Conditions of applicability

- (a) a precise allocation of the design lower cyclic load, N_{Elod} , is possible and/or
- (b) an upper limit of load cycles, n , during working life is known.

Based on (a) and (b), the following values shall be used for design:

Design Case 1: Only condition (a) is met:

$$\Delta N_{Rd,E,n} = \Delta N_{Rd,E,\infty}$$

The fatigue resistance used in the design verification is determined using the Goodman Diagram assuming an infinite number of cycles, $n = \infty$, and the appropriate value of the lower cyclic load, N_{Elod} , in accordance with Section 3.2.2 Equation (3.6)

and

$$\Delta N_{Ed} = N_{Eupd} - N_{Elod}$$

Only the design fatigue relevant load is taken into account.

Design Case 2: Only condition (b) is met:

$$\Delta N_{Rd,E,n} = \Delta N_{Rd,0,n}$$

The fatigue resistance used in the design verification is taken from the S-N curve for the given number of load cycles n .

and

$$\Delta N_{Ed} = N_{Eupd}$$

All acting loads are assumed to be fatigue-relevant.

Design Case 3: Conditions (a) and (b) are both met:

$$\Delta N_{Rd,E,n}$$

The fatigue resistance used in the design verification is determined using the Goodman Diagram for the given number of load cycles, n , and the appropriate value of the lower cyclic load, N_{Elod} , in accordance with Section 3.2.2 Equation (3.5)

and

$$\Delta N_{Ed} = N_{Eupd} - N_{Elod}$$

Only the design fatigue relevant load is taken into account.

3.2.2 Calculation of fatigue resistance, $\Delta N_{Rd,E,n}$, in relation to the lower cyclic load, N_{Eload}

The fatigue resistance diagram (also known as S-N curve) is determined experimentally with cyclic load tests where a constant minimum lower load as low as possible is used (i.e., the contribution or influence of the lower cyclic load to the total applied load is minimized). This procedure allows the determination of the characteristic fatigue resistance, $\Delta N_{Rk,0,n}$, for a given number of load cycles, n , and for each failure mode.

In cases where actions consist of a combination of a non-negligible lower cyclic load and a fatigue (cyclic) relevant part, it is necessary to determine the influence of the lower cyclic load on the fatigue resistance. This is achieved by using the Goodman Diagram, which allows the determination of the fatigue resistance as a function of the magnitude of the applied lower cyclic load. The fundamental principles of the Goodman Diagram are valid for every type of failure mode.

Note: The definition of the lower cyclic load, N_{Eload} , depends on the following cases (see also Figure 3.1):

- a) *the static load, N_{Ed} , is amplified by the cyclic load ΔN_{Ed} , meaning that N_{Eload} corresponds to N_{Ed} ;*
- b) *the static load, N_{Ed} , is superimposed with the cyclic load resulting in N_{Eload} being smaller than N_{Ed} ;*
- c) *the static load, N_{Ed} , is reduced by the cyclic load, meaning that N_{Eload} corresponds to $N_{Ed} - \Delta N_{Ed}$.*




Figure 3.1 Superimposition of static and fatigue cyclic loads

Figure 3.2 shows the Goodman Diagram for a selected number of oscillation cycles n . N_{Eload} is the lower cyclic load and $\Delta N_{Rd,E,n}$ is the corresponding fatigue resistance. The design fatigue resistance, $\Delta N_{Rd,0,n}$, with lower cyclic load, N_{Eload} , equal to zero for n load cycles and the static resistance, N_{Rd} , can be derived by applying the appropriate material partial safety factors to the characteristic values.




Figure 3.2 Goodman Diagram. Example for the determination of the fatigue resistance as a function of the lower cyclic load ($N_{Eload} \geq 0$)

Note: For oscillations with the same algebraic sign the design value of the fatigue resistance for n cycles, $\Delta N_{Rk,E,n}$, and the fatigue limit resistance, $\Delta N_{Rk,E,\infty}$, is calculated according to Equations (3.5) and (3.6), respectively.

$$\Delta N_{Rd,E,n} = \Delta N_{Rd,0,n} \cdot \left(1 - \frac{N_{Eload}}{N_{Rd}}\right) \quad (3.5)$$

$$\Delta N_{Rd,E,\infty} = \Delta N_{Rd,0,\infty} \cdot \left(1 - \frac{N_{Eload}}{N_{Rd}}\right) \quad (3.6)$$

3.2.3 Required verifications for design

Design case 1: Steel failure: $(\Delta N_{Ed} / \Delta N_{Rd,s,E,\infty}) \leq 1,0$ (3.7)

Pull-out: $(\Delta N_{Ed} / \Delta N_{Rd,p,E,\infty}) \leq 1,0$ (3.8)

Concrete cone: $(\Delta N_{Ed} / \Delta N_{Rd,c,E,\infty}) \leq 1,0$ (3.9)

Design case 2: Steel failure: $(\Delta N_{Ed} / \Delta N_{Rd,s,0,n}) \leq 1,0$ (3.10)

Pull-out: $(\Delta N_{Ed} / \Delta N_{Rd,p,0,n}) \leq 1,0$ (3.11)

Concrete cone: $(\Delta N_{Ed} / \Delta N_{Rd,c,0,n}) \leq 1,0$ (3.12)

Design case 2: Steel failure: $(\Delta N_{Ed} / \Delta N_{Rd,s,E,n}) \leq 1,0$ (3.13)

Pull-out: $(\Delta N_{Ed} / \Delta N_{Rd,p,E,n}) \leq 1,0$ (3.14)

Concrete cone: $(\Delta N_{Ed} / \Delta N_{Rd,c,E,n}) \leq 1,0$ (3.15)

3.3 Design method II – Simplified method

3.3.1 Conditions of applicability

A precise allocation of the design lower cyclic load, N_{Eload} , is not possible and an upper limit to the number of load cycles, n , over the working life of the fastener cannot be predicted.

Therefore, the following values shall be used for design:

$$\Delta N_{Rd,E;n} = \Delta N_{Rd,0,\infty}$$

The fatigue resistance used in the design verifications is the design value of fatigue limit resistance with an origin load ($N_{Eload} = 0$).

and

$$\Delta N_{Ed} = N_{Eupd}$$

All acting loads are assumed to be fatigue-relevant.

3.3.2 Required verifications for design

Steel failure: $(\Delta N_{Ed} / \Delta N_{Rd,s,0,\infty}) \leq 1,0$ (3.16)

Pull-out: $(\Delta N_{Ed} / \Delta N_{Rd,p,0,\infty}) \leq 1,0$ (3.17)

Concrete cone: $(\Delta N_{Ed} / \Delta N_{Rd,c,0,\infty}) \leq 1,0$ (3.18)

4 REFERENCE DOCUMENTS

- [1] EN 1992-1-1:2004+AC:2010: Design of concrete structures. Part 1-1: General rules and rules for buildings
- [2] EN 1992-4:2018: Design of concrete structures; Part 4: Design of fastenings for use in concrete
- [3] EAD 330008-03-0601: Anchor channels
- [4] EOTA TR 047:2018: Calculation method for the performance of anchor channels
- [5] EN 206-1+A1+A2:2000: Concrete - Specification, performance, production and conformity
- [6] Miner, M., A.: Cumulative Damage in Fatigue, Journal of Applied Mechanics, 12 (1945), 159-164